Bohnenkamp Moving Professionals

BKT



10.0/75-15.3 (10/75-15.3) 18PR BKT AW 909 135A8 TL 10/75-15.3

Product-No.: R00413

Technical Information:

| Product number | R00413 |
|--------------------------|--------------|
| Tyre size | 10.0/75-15.3 |
| TL / TT | TL |
| LI / SI | 135A8 |
| PR | 18 |
| Tread | AW 909 |
| Brand | ВКТ |
| Specification | (10/75-15.3) |
| Recommended rim | 9.00 |
| Width mm | 274 |
| Outer diameter mm | 760 |
| static radius mm | 343 |
| Rollsize mm | 2227 |
| Loadindex kg/at km/h (1) | 2180 / 40 FR |
| Loadindex kg/at km/h (2) | 2595 / 25 FR |
| Inflation pressure bar | 7.1 |
| Weight kg | 17.32000 |
| Volume m3 | 0.11000 |

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Supplier does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.