Bohnenkamp Moving Professionals

DEESTONE



29.5-25 28PR DEESTONE D313 207A2/193B E-3/L-3 TL

Product-No.: 293882

Technical Information:

Product number	293882
Tyre size	29.5-25
TL / TT	TL
LI / SI	207A2/193B
PR	28
Tread	D313
Brand	Deestone
Recommended rim	25.00/3.5
Allowed rim	
Width mm	738
Width mm Outer diameter mm	738 1854
Outer diameter mm	1854
Outer diameter mm Loadindex kg/at km/h (1)	1854 17500 / 10 / 4,25 bar
Outer diameter mm Loadindex kg/at km/h (1) Loadindex kg/at km/h (2)	1854 17500 / 10 / 4,25 bar 11500 / 50 / 3,25 bar
Outer diameter mm Loadindex kg/at km/h (1) Loadindex kg/at km/h (2) Inflation pressure bar	1854 17500 / 10 / 4,25 bar 11500 / 50 / 3,25 bar 4.25
Outer diameter mm Loadindex kg/at km/h (1) Loadindex kg/at km/h (2) Inflation pressure bar Weight kg	1854 17500 / 10 / 4,25 bar 11500 / 50 / 3,25 bar 4.25 370.00000

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Supplier does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.